STONE



TYPE 41

STANDARD FLAT CUTTING DISCS FOR PORTABLE ANGLE GRINDERS





GLOBE offers a wide range of standard flat cutting wheels of 2,5 mm thickness for portable grinders. Of great importance is the right choice for the work to be done. This range is suitable for heavy works for which thin discs are not the right product. Choosing the right product is essential. The different types of abrasives, different binders and different hardnesses are the fundamentals to always supply the maximum performance to any application. The several combinations offered by GLOBE range always allow to find the best product for the work to be carried out.

MATERIAL	DIMENSIONS (diam - thick bore) mm	HARDNESS	USE SPEED	ARTICLE CODE		PLUS LINE	
STAINLESS STEEL AND STEEL	A 30-36 Q: for standard use in cutting iron and steel. Good cutting capacity and medium durability. Usable also on stainless steel.					DISC DURABILITY CUTTING SPEED CLEAN CUT	••••• •••••
	230x2,5x22,23	A 30-36 Q	80 m/s	G1415 •	25pcs	CLLANCOI	
STEEL	A 30-36 R: for cutting iron and steel. Offers a good cutting capacity and long durability. Excellent resistance to stress.					DISC DURABILITY CUTTING SPEED CLEAN CUT	••••• •••••
	100x2,5x16,00	A 30-36 R	80 m/s	G1421	50pcs	CELAN COT	
	115x2,5x22,23	A 30-36 R	80 m/s	G1422	50pcs		
	125x2,5x22,23	A 30-36 R	80 m/s	G1423 •	50pcs		
•	125x2,5x22,23 230x2,5x22,23	A 30-36 R A 30-36 R		G1423 • G1425 •	50pcs 25pcs		
STEEL		A 30-36 R d with special resin	80 m/s	G1425 • orasives. Offers a	25pcs		
STEEL	230x2,5x22,23 A 30-36 T: manufacture lent cutting capacity, lo	A 30-36 R d with special resin	80 m/s	G1425 • orasives. Offers a	25pcs		
STEEL	230x2,5x22,23 A 30-36 T: manufacture lent cutting capacity, lo heavy stress.	A 30-36 R d with special resing durability and o	80 m/s as and abexcellent 80 m/s	G1425 • prasives. Offers a tresistance to the	25pcs n excel- ne most		
STEEL STAINLESS STEEL	230x2,5x22,23 A 30-36 T: manufacture lent cutting capacity, lo heavy stress. 180x2,5x22,23	A 30-36 R d with special resing durability and of the special resing durability and of the special resing durability and of the special resingular special resingular residual residua	80 m/s s and abexcellent 80 m/s 80 m/s rconia for and iron	G1425 • prasives. Offers at resistance to the r	25pcs n excel- ne most 25pcs 25pcs eel and	DISC DURABILITY CUTTING SPEED CLEAN CUT	••••• •••• ••••
STAINLESS	230x2,5x22,23 A 30-36 T: manufacture lent cutting capacity, lo heavy stress. 180x2,5x22,23 230x2,5x22,23 Z 30-36 SX: wheel constainless steel. Without	A 30-36 R d with special resing durability and of the special resing durability and of the special resing durability and of the special resingular special resingular residual residua	80 m/s as and absexcellent 80 m/s 80 m/s rconia for and iron ting, long	G1425 • prasives. Offers at resistance to the r	25pcs n excel- ne most 25pcs 25pcs eel and	CUTTING SPEED	
STAINLESS	230x2,5x22,23 A 30-36 T: manufacture lent cutting capacity, lo heavy stress. 180x2,5x22,23 230x2,5x22,23 Z 30-36 SX: wheel constainless steel. Without tion available). Excellent	A 30-36 R d with special resing durability and december of the special resing durability and december of the special resing alumina zing alumina zing sulphur, chlorine toold and fast cut	80 m/s s and absexcellent 80 m/s 80 m/s reconia for and iron ting, lon 80 m/s	orasives. Offers at resistance to the 7325115370100 G1435 or use on alloy stance of compounds (compounds (compounds))	25pcs n excel- ne most 25pcs 25pcs eel and ertifica-	CUTTING SPEED	
STAINLESS	230x2,5x22,23 A 30-36 T: manufacture lent cutting capacity, lo heavy stress. 180x2,5x22,23 230x2,5x22,23 Z 30-36 SX: wheel constainless steel. Without tion available). Excellent	A 30-36 R d with special resing durability and of the special resing durability and of the special resing durability and of the special residual r	80 m/s s and absexcellent 80 m/s 80 m/s rconia for and iror ting, lon 80 m/s 80 m/s	G1425 • prasives. Offers at resistance to the resistance to the resistance at resista	25pcs n excel- ne most 25pcs 25pcs 25pcs eel and ertifica-	CUTTING SPEED	

80 m/s G1452

80 m/s G1453

80 m/s G1455 •

50pcs

25pcs

25pcs

ting capacity, medium hardness and long durability.

C 30-36 RE

C 30-36 RE

C 30-36 RE

115x2,5x22,23

125x2,5x22,23

230x2,5x22,23

CUTTING SPEED

CLEAN CUT