


CUTTING (Ø > 230mm)



TYPE 41

# CHOPCUT FLAT DISCS FOR LIGHT BENCH GRINDERS



**CHOPCUT** cutting discs for light stationary machines allow to cut sections' profiles, tubes and also full sections with diameter up to 30/40 mm. They combine a long durability with an excellent cutting capacity thanks to their low thickness. Particular care is taken in balancing these discs to ensure comfortable cutting operations and a good grinder stability without vibrations.

| MATERIAL               | DIMENSIONS<br>(diam - thick. - bore) mm   | HARDNESS   | USE<br>SPEED | ARTICLE<br>CODE |       | PLUS LINE | DISC DURABILITY  | CUTTING SPEED | CLEAN CUT |
|------------------------|---|------------|--------------|-----------------|-------|-----------|--|---------------|-----------|
| <b>STEEL</b>           | <b>A 30-36 S (CHOPCUT):</b> for iron and steel. Universal cutting discs, long durability and high cutting speed. Suitable for cutting sections' profiles and medium sized full sections.  |            |              |                 |       |           | <br>DISC DURABILITY ●●●●●●<br>CUTTING SPEED ●●●●●●<br>CLEAN CUT ●●●●●● |               |           |
|                        | 300x2,5x25,40   | A 30-36 S  | 80 m/s       | G1911 •         | 25pcs |           |  |               |           |
|                        | 350x3,0x25,40   | A 30-36 S  | 80 m/s       | G1912 •         | 25pcs |           |  |               |           |
|                        | 400x3,2x25,40   | A 30-36 S  | 80 m/s       | G1913           | 10pcs |           |  |               |           |
| <b>STAINLESS STEEL</b> | <b>A 30-36 SX (CHOPCUT):</b> for stainless steel, free from iron, sulphur and chlorine compounds (certification available). Long durability and excellent cutting capacity. Suitable for cutting sections' profiles and medium sized full sections. |            |              |                 |       |           | DISC DURABILITY ●●●●●●<br>CUTTING SPEED ●●●●●●<br>CLEAN CUT ●●●●●●     |               |           |
|                        | 300x2,5x25,40   | A 30-36 SX | 80 m/s       | G1911-INOX      | 25pcs |           |  |               |           |
|                        | 350x3,0x25,40   | A 30-36 SX | 80 m/s       | G1912-INOX      | 25pcs |           |  |               |           |
|                        | 400x3,2x25,40   | A 30-36 SX | 80 m/s       | G1913-INOX      | 10pcs |           |  |               |           |

| MATERIAL     | DIMENSIONS<br>(diam - thick. - bore) mm  | HARDNESS  | USE<br>SPEED | ARTICLE<br>CODE |       | DYNAMIC LINE | DISC DURABILITY  | CUTTING SPEED | CLEAN CUT |
|--------------|--|-----------|--------------|-----------------|-------|--------------|--|---------------|-----------|
| <b>STEEL</b> | <b>A 30-36 S:</b> universal cutting discs, suitable for cutting thin sections' profiles and full sections. |           |              |                 |       |              | <br>DISC DURABILITY ●●●●○○<br>CUTTING SPEED ●●●●○○<br>CLEAN CUT ●●●●○○ |               |           |
|              | <b>NEW</b> 300x4,0x25,40   | A 30-36 S | 80 m/s       | G1911 DYN       | 25pcs |              |  |               |           |
|              | <b>NEW</b> 350x4,0x25,40   | A 30-36 S | 80 m/s       | G1912 DYN       | 25pcs |              |  |               |           |

• = articles always in stock