



TUNGSTEN CARBIDE ROTARY BURRS FOR PORTABLE STRAIGHT GRINDERS OR DRILLS



DESCRIPTION OF CUTS

Cut 1A (aluminium): Suitable for aluminium and aluminium alloys as well as plastics.	Cut 1 (DIN C): Suitable for deburring non-hardened steels, soft steels, alloys and hard plastics.	Cut 2: Suitable for steels with high tensile strength, inox, cast steels, welding seams and brass

DESCRIPTION OF CUTS

Cut 3 (DIN MY): For general purposes such as deburring, chamfering and smoothing edges with clean surface. Suitable for steels with high tensile strength and welding seams	Cut 4 (diamond): Suitable for hardened steels with excellent surface quality and welding seams with high tensile strength.	Cut 6 (DIN MX): With this universal cutting profile even hardest materials and welding seams can be machined with best finishing quality. Ideal for the tool and mould industry.

TUNGSTEN CARBIDE ROTARY BURRS

	FRONT CUT												
Type	ZYA	ZYA-S	WRC	SPG	WKN	SKM	KSK	KSJ	TRE	KUD	RBF	KEL	B
Type ISO	A	A-S	C	G	N	M	K	J	E	D	F	L	H
Ø mm	2-20	2-20	3-20	3-16	3-12	3-16	3-20	3-16	3-16	2,5-20	3-20	3-16	6-16

CUTTING PROFILE

Cutting Profile	ZYA	ZYA-S	WRC	SPG	WKN	SKM	KSK	KSJ	TRE	KUD	RBF	KEL	B
1A Aluminium	●	●	●	●						●	●	●	
1 DIN C			●								●	●	
2	●	●	●	●		●				●	●	●	
3 DIN MY	●	●	●	●	●	●	●	●	●	●	●	●	●
4 Diamond	●	●	●	●	●	●			●	●	●	●	●
6 DIN MX	●	●	●	●	●	●	●	●	●	●	●	●	●

▼ = articles always in stock

● = available in 20 days